## **TC Series**

## **Tire Changers**

## **HUNTER Engineering Company**

## SITE REQUIREMENTS



	TC39 Family	TC37 Family
Electrical Circuit Requirements	208-230V, 6A, 50/60Hz, 1 ph NEMA 20 amp plug, L6-20P	
Air Supply Requirements	115-145 psi (8-10 bar)	
Approximate Air Consumption	4 CFM (110 Liters/Minute)	
Base Machine Weight	770 lbs (349 kg)	787 lbs (357 kg)
Wheel Lift Weight	62 lbs (28 kg)	
Side Shovel Weight	92 lbs (42 kg)	
Width (W)	55 in. (1,397 mm)*	
Height (H)	77 in. (1,956 mm)	72 in. (1,829 mm)
Depth (D)	58 in. (1,473 mm)	
Power Cord Length	~110 in. (2,794 mm)	


\* Add 14 in. (356 mm) for maximum side shovel opening (if equipped)


**TC37 Family** 



	1 000 i aiiiiiy	1007 I dillily
Mount / Demount Tool	Polymer Self-inserting leverless	Polymer Standard lever mount head
Clamping Type	Center w/ Quick Clamp and Cam Plate	
Bead Loosening Type	Upper & Lower Rollers (Shovel Optional)	
Match Mounting Capable	Yes	
Adjustable Clamping Height	Yes, 3 position	
Rim Diameter Range	10-26 in.	
Maximum Tire Diameter	46 in.	
Maximum Wheel Width	19 in.	
Drive Speed	Fully Variable, 0-14 RPM Clockwise Single Speed, 7 RPM Counterclockwise	

TC39 Family





**Drive Torque** 

**Wheel Lift Capacity** 

**KEY SPECIFICATIONS** 

For tire changer information visit: www.hunter.com/tire-changers

867 ft-lb (1175 N-m)

176 lbs (80 kg)

For local contest visits

For local contact visit: www.hunter.com/contact-hunter

For general inquiries visit: www.hunter.com or call 800-448-6848