

R560 MOBILE HD


MOBILE TIRE CHANGER

**EASY-TO-USE COMMERCIAL
TRUCK TIRE CHANGER**




Set up this changer for both roadside and workshop service. Suitable for mobile use in closed vans and working from small workshops.

- ALL controls on operator console
- Fast cycle times
- Adjustable hydraulic clamping and chucking table
- Suitable for agricultural tries with optional wheel disc
- Service tire diameters up to 51"



HYDRAULIC HEIGHT POSITIONING

- Raise or lower the wheel clamps depending on the wheel diameter



4" minimum clamping
13" minimum height

Designed to clamp a variety of wheels, including those for agriculture tires.



Roller and overhead arm easily adjust for bead removal

SINGLE ADJUSTABLE ROLLER


- Easy to set roller works for breaking both rear and front tire beads
- Optimized aluminum roller works for tube tires

THE MOBILE TIRE CHANGER
DESIGNED FOR SMALL SHOPS



QUICK LOADING
SLIDING TIRE RAMP

TIRE DIMENSIONS



**WATCH
& LEARN!**
Scan code to watch
product videos.



ROTARY[®]

BY ROTARY SOLUTIONS

R560 MOBILE HD COMMERCIAL TIRE CHANGER

FEATURES

- Service steel and alloy rims
- Hydraulic clamping / chucking table
- Tire paste lubricant and brush
- Ships with NEMA L6-20P plug

R560 services:



Optional equipment may be required


SPECIFICATIONS:

Chucking unit rotation motor	1.5 Hp / 1.1 kW
Hydraulic drive unit motor	2.7 Hp / 2 kW
Rim diameter	11" - 27"
Maximum tire diameter	51" (1300mm)
Maximum tire width	37.4" (950mm)
Bead breaker power	3,597 Ft / Lbs / 16000 N
Maximum assembly weight	2,645 lbs / 1200 kg
Chuck rotation speed (rev/min)	6.5
Maximum torque to chuck	1253 Ft / Lbs / 1700 Nm
Power supply	220v / 1Ø / 60 Hz


Site Requirements: 220V / 1Ø / 60 Hz power supply

ROTARY WHEEL SERVICE EQUIPMENT carries a 3 year warranty. See website for details.

STANDARD ACCESSORIES



VSG108A2
Standard clamp protections for alloy rims / 4 x kit




Aluminum rim protection using attachable braces on hydraulic clamps



VSG90A6
Aluminum rim clamp



VSG108A3 Tire Lever



VSG108A25
Steel rim clamp



B5308000
Long bead lifting lever

OPTIONAL ACCESSORIES



VSG108A22
Disc for wheels with lock ring

VSG108A24
Disc for wheels with lock ring / agricultural wheels



VSG108A34
Pneumatic bead pushing device



ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at www.RotarySolutions.com today.

Need assistance or have questions? We're here to help:
800.445.5438 / Sales: insidesales@rotarysolutions.com
Technical Support: WS-techsupport@rotarysolutions.com

ROTARY SOLUTIONS™

2700 Lanier Drive | Madison, IN 47250, U.S.A.

Lit# Rotary.R560.Cutsheet.10.01.2024

©2024 VEHICLE SERVICE GROUP™
All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS™, VEHICLE SERVICE GROUP™, DOVER® and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.